





New in 2016, Power Acoustik introduces the Incite series head units. Incite operating systems use an advanced microprocessors and central processing unit bringing lightning fast reaction time into automotive multimedia entertainment systems. Premium Incite units feature built-in advanced GPS Navigation with MobileLink 2-way MHL complete smart phone integration, or Sirius/XM satellite radio ready interface. Standards for all Incite models include Bluetooth V3.0 for hands-free calling, Adaptive

Fast Charging of enabled mobile devices, and more. Select Incite units add multi-color illumination or an advanced audio staging equalizer. Each universal 2-DIN model uses a 6.2" Active Matrix LCD display with adjustable LED backlighting. 1-DIN models available in summer 2016 include motorized 7" and detachable 3.4" LCD.



Adaptive Fast Charging

We demand top performance of our mobile devices to meet our social media and content streaming needs. To keep up with rapidly changing design trends, our mobile devices tend to rely on limited energy capacity, utilizing every efficiency to prolong the charge of the battery. AptiX source units feature USB Adaptive Fast Charge technology, reducing necessary down time to get you moving again. AFC has the potential to recharge enabled mobile device batteries from zero to up to 50% in about 30 minutes. (USB cable not included)



Bluetooth V3.0 Hands-Free Calling

Bluetooth V3.0 with Enhanced Data Rate increases traditional data transfer rates to 2.1 Mbit/s. This lightning quick information transfer increases clarity & virtually eliminates unwanted distortion during calls and wireless MP3 audio playback. Most Bluetooth enabled Smartphones will transfer phone book contacts, view recent call logs, and stream MP3 audio tracks.

PD-621XB

2-DIN DVD, Sirius/XM Ready, Bluetooth, CD/USB/MP3 Car Stereo w/ 6.2" LCD







ADDITIONAL SERIES DETAILS:

Bluetooth V3.0 Hands-Free Calling from Enabled Phone A2DP Wireless MP3 Audio Playback from Enabled Device Built-in Microphone & External Microphone Included Accepts OEM Steering Wheel Control Interfaces Advanced FM/AM Tuner with RDBS Playback from DVD & CD of MP3 & MP4 Playback from 64GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track & Artist Information AUX Audio Input for Personal Media Devices

PDN-621HB

2-DIN GPS Navigation, MHL MobileLink X2, DVD, Bluetooth, CD/USB/MP3 Car Stereo w/ 6.2" LCD



Multi-band Audio Equalizer w/ Presets Front & Rear Pre-Amp Audio Outputs Variable Subwoofer Pre-Amp Output Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 300w 4ch. MOSFET Speaker Outputs Custom Backgrounds & Screen Savers Multi-Region FM Frequency Stepping 800x480 Widescreen Resolution 400NIT LED Backlight

INCITE SOURCE UNITS

Digital Signal Processing features include a digital 10-band equalizer with 14dB boost or cut, custom presets, & factory presets. Additional DSP functions include variable subwoofer level control, reverb optimization, loudness adjustment, & sound staging controls.



MOBILE LINK X2 AVN SOURCE UNITS



MobileLink X2 AVN models feature GPS turn-by turn navigation for USA, Canada, & Mexico. Set your destination and follow the commands by text-to-speech directions, including lane guidance. Additional features include favorites list, programmable home destination, destination fuel estimates, multi-lingual, multi-gender voices, speed limit warnings, and more.

PDN-626B

2-DIN GPS Navigation, MHL MobileLink X2, DVD, Bluetooth, CD/USB/MP3 Car Stereo w/ 6.2" LCD



PDN-726B

1-DIN GPS Navigation, MHL MobileLink X2, DVD, Bluetooth, CD/USB/MP3 Car Stereo w/ Motorized 7" LCD



12 Million Points of Interest Database Included Complete Integration of Select Android Enabled Devices Bluetooth V3.0 Hands-Free Calling from Enabled Phone A2DP Wireless MP3 Audio Playback from Enabled Device Built-in Microphone & External Microphone Included Accepts OEM Steering Wheel Control Interfaces





MHL MobileLink X2 mobile device integration enables complete control of your smartphones and tablets. Conveiently launch any application, post social media updates, or play your own videos and all other content on your mobile device. Your smart device display is mirrored to the head units larger LCD screen via USB, and all commands are sent via Bluetooth 3.0 connection. MHL MobileLink X2 ensures safe, hands-free operation of your smart device without the distractions of locating & handling the device.





Bluetooth V3.0 with Enhanced Data Rate increases traditional data transfer rates to 2.1 Mbit/s. This lightning quick information transfer increases clarity & virtually eliminates unwanted distortion during calls and wireless MP3 audio playback.

. Digital Signal Processing features include a digital 10-band equalizer with 14dB boost or cut, custom presets, & factory presets. Additional DSP functions include variable subwoofer level control, reverb optimization, loudness adjustment, & sound staging controls.



MHL MobileLink Interface Cables HDM-i4 ~ iPhone4, iPhone4S, iPad2, & iPad3 HDM-A2 ~ Galaxy 2 & Select 5-Pin Android Devices

HDM-A3 ~ Galaxy 3, 4, 5, & Select 11-PIN Android Devices

5ft interface cable unlocks 1080p video and audio playback from MHL enabled appropriate micro connector for your mobile device. Farenheit MobileLink MHL interface cables also charge your mobile device. Available for select iOS and Android devices.



MOBILE LINK X2 AVN







Advanced FM/AM Tuner with RDBS Playback from DVD & CD of MP3 & MP4 Plavback from 64GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track Information AUX Audio Input for Personal Media Devices 10-Band Audio Equalizer w/ User Presets Front & Rear Pre-Amp Audio Outputs Variable Subwoofer Pre-Amp Output

Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 300w 4ch. MOSFET Speaker Outputs Custom Backgrounds & Screen Savers Multi-Region FM Frequency Stepping 800x480 Widescreen Resolution 400NIT LED Backlight



the distractions of locating & handling the device. MHL MobileLink X2 integration cables are available for select Android enabled devices.



PD-62H2B

2-DIN MHL MobileLink X2, DVD, Bluetooth, CD/USB/MP3 Car Stereo w/ 6.2" LCD







PD-72H2B

1-DIN MHL MobileLink X2, DVD, Bluetooth, CD/USB/ MP3 Car Stereo w/ Motorized 7" LCD









ADDITIONAL SERIES DETAILS:

Complete Integration of Select Android Enabled Devices (requires MHL MobileLink accessory cable, sold separate) Bluetooth V3.0 Hands-Free Calling from Enabled Phone A2DP Wireless MP3 Audio Playback from Enabled Phone Built-in Microphone & External Microphone Included Accepts OEM Steering Wheel Control Interfaces















Bluetooth V3.0 with Enhanced Data Rate increases traditional data transfer rates to 2.1 Mbit/s. This lightning guick information transfer increases clarity & virtually eliminates unwanted distortion during calls and wireless MP3 audio playback. Most Bluetooth enabled Smartphones will transfer phone book contacts, view recent call logs, and stream MP3 audio tracks.

MHL MobileLink X2 mobile device integration enables com-

plete control of your smart-

phones and tablets. Conveiently

launch any application, post social media updates, or play your own videos and all other con-

tent on your mobile device. Your smart device display is mirrored

to the head units larger LCD

screen via USB, and all com-

mands are sent via Bluetooth 3.0

connection. MHL MobileLink X2 ensures safe, hands-free operation of your smart device without



MHL MobileLink Interface Cables

HDM-i4 ~ iPhone4, iPhone4S, iPad2, & iPad3

HDM-A2 ~ Galaxy 2 & Select 5-Pin Android Devices

HDM-A3 ~ Galaxy 3, 4, 5, & Select 11-PIN Android Devices



5ft interface cable unlocks 1080p video and audio playback from MHL enabled appropriate micro connector for your mobile device. Farenheit MobileLink MHL interface cables also charge your mobile device. Available for select iOS and Android devices.



MOBILE LINK X2





Advanced FM/AM Tuner with RDBS Receiver Playback from DVD & CD of MP3 & MP4 Playback from 64GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track Information AUX Audio Input for Personal Media Devices Front & Rear Pre-Amp Audio Outputs Variable Subwoofer Pre-Amp Output

Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 300w 4ch. MOSFET Speaker Outputs Multi-Region FM Frequency Stepping 800x480 Widescreen Resolution 400NIT LED Backlight



4



*MHL

MHL MobileLink X1 opens mirroring of smartphones and tablets to enabled in-car entertainment systems. Share with other passengers your own movies, social networking content, internet videos, or anything else your mobile device displays. Easily follow your smartphone's navigation commands on the larger head unit LCD instead of the smaller smart phone display. MHL MobileLink X1 replicates the image of your smart device onto the LCD screen of several in-car entertianment products, including select MobileLink X1 source units, headrests, and overhead displays. MHL MobileLink integration cables are available for select Android and iOS smart devces.



🐵 🖲 🛥 🕴 12:46 мм 🧐



Bluetooth V3.0 with Data Enhanced Rate increases traditional data transfer rates to 2.1 Mbit/s. This lightning quick information

transfer increases clarity & virtually eliminates unwanted distortion during calls and wireless MP3 audio playback. Most Bluetooth enabled Smartphones will transfer phone book contacts, view recent call logs, and stream MP3 audio tracks.



Customizing options include several preloaded background images & color changing graphic user interface. Select models include variable color front panel illumination. Choose a specific color to match your interior lighting scheme or random color change for a full color spectrum effect.

MHL MobileLink Interface Cables

HDM-i4 ~ iPhone4, iPhone4S, iPad2, & iPad3 HDM-A2 ~ Galaxy 2 & Select 5-Pin Android Devices HDM-A3 ~ Galaxy 3, 4, 5, & Select 11-PIN Android Devices

5ft interface cable unlocks 1080p video and audio playback from MHL enabled appropriate micro connector for your mobile device. Farenheit MobileLink MHL interface cables also charge your mobile device. Available for select iOS and Android devices.







PD-624HB

2-DIN MHL MobileLink X1, DVD, Bluetooth, CD/USB/MP3 Car Stereo w/ 6.2" LCD



CHANGEABLE **ILLUMINATION**

PD-724HB

1-DIN MHL MobileLink X1, DVD, Bluetooth, CD/USB/MP3 Car Stereo w/ Motorized 7" LCD



ADDITIONAL SERIES DETAILS:

On-Screen Mirroring of Select Android Smart Devices (requires MHL MobileLink accessory cable, sold separate) Bluetooth V3.0 Hands-Free Calling from Enabled Phone A2DP Wireless MP3 Audio Playback from Enabled Devices Accepts OEM Steering Wheel Control Interfaces Custom Backgrounds & RGB Color Changing GUI Advanced FM/AM Tuner with RDBS Receiver

MOBILE LINK X1 SOURCE UNITS





Playback from DVD & CD of MP3 & MP4 Playback from 32GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track & Information AUX Audio Input for Personal Media Devices RCA A/V Input for Auxiliary Sources 4-Band Audio Equalizer w/ User Presets Front & Rear Pre-Amp Audio Outputs Variable Subwoofer Pre-Amp Output

Variable Subwoofer Low Pass Crossover Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 300w 4ch. MOSFET Speaker Outputs Multi-Region FM Frequency Stepping 800x480 Widescreen Resolution 400NIT LED Backlight





Million Color

Bluetooth V3.0 with Enhanced Data Rate increases traditional data transfer rates to 2.1 Mbit/s. This lightning quick information transfer increases

clarity & virtually eliminates unwanted distortion during calls and wireless MP3 audio playback. Most Bluetooth enabled Smartphones will transfer phone book contacts, view recent call logs, and stream MP3 audio tracks.

Customizing options include several preloaded background images & color changing graphic

user interface. Select models include variable color front panel illumination. Choose a specific color to match your interior lighting scheme or random color

1	2	3	×	-0
4	5	6		
7	8	9		=
*	0	#		•

← FM1 104.60 P5 →

87.50 90.10 98.10 106

((M) (L)

💿 🖩 🔹 🕴 12:46 ам 🧐

RED

< SETUP ILLUMINATION

<	IT MU	SIC	0		-681	*	12:	46ам	0
	 USER	勳	DX	Ø	SWF	TA	AF	LOUD	
			в	LUET	гооті	ł			
		K	1			i.			

💿 🖩 🔹 🕴 12:46 мм 😲

(0,0)

(·· FMI 104.60 PS ··)

87.50 90.10 98.10 106.10 104.60 87.50

(1)



1-DIN DVD, CD/MP3, SD/USB, AM/FM Receiver, w/ Motorized 7" LCD, & Bluetooth



change for a full color spectrum effect.

PD-624B 2-DIN DVD, CD/MP3, SD/USB, AM/FM Receiver, w/ 6.2" LCD, & Bluetooth



PD-454B

1-DIN DVD, CD/MP3, SD/USB, AM/FM Receiver w/ Detachable 4.5" LCD & Bluetooth





ADDITIONAL SERIES DETAILS: Bluetooth V3.0 Hands-Free Calling from Enabled Phone A2DP Wireless MP3 Audio Playback from Enabled Phone Accepts OEM Steering Wheel Control Interfaces Custom Backgrounds & RGB Color Changing GUI

Advanced FM/AM Tuner with RDBS Receiver

Playback from DVD & CD of MP3 & MP4

MULTIMEDIA SOURCE UNITS

Playback from 32GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track & Information AUX Audio Input for Personal Media Devices RCA A/V Input for Auxiliary Sources 4-Band Audio Equalizer w/ User Presets Front & Rear Pre-Amp Audio Outputs Variable Subwoofer Low Pass Crossover

Variable Subwoofer Pre-Amp Output Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 300w 4ch. MOSFET Speaker Outputs Multi-Region FM Frequency Stepping 800x480 Widescreen Resolution 400NIT LED Backlight



PD-651B

2-DIN Multimedia Source Unit w/ 6.5" LCD Touch Screen w/ Bluetooth









PTID-8920B





PD-710 PD-710B (w/ Bluetooth V2.0) 1-DIN Multimedia Source Unit w/ Detachable 7" LCD Touch Screen





4CH. AMPLIFIER

Bluetooth DVD





ADDITIONAL SERIES DETAILS:

Bluetooth V2.0 Hands Free Calling From Enabled Devices A2DP Wireless MP3 Audio Playback From Enabled Devices Accepts OEM Steering Wheel Control Interface Playback from DVD & CD of MP3 & MP4 Playback from 32GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track & Artist Information AUX A/V Input for Personal Media Devices Front & Rear Pre-Amp Audio Outputs



Subwoofer Pre-Amp Audio Output Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 300w 4ch. MOSFET Speaker Outputs Custom & Preset Equalizer Settings Multi-Region FM Frequency Stepping 800x480 Widescreen Resolution 400 NIT LED Brightness

12

MULTIMEDIA SOURCE UNITS

1-DIN Multimedia Source Unit w/ 7" Flip-Up LCD Touch Screen w/ Bluetooth





PD-344 PD-344B (w/ Bluetooth V2.0) 1-DIN A/V Source Unit w/ Detachable 3.4" LCD Screen



1-DIN Multimedia Receiver w/ High Definition 3.4" LCD Display Theft Deterrent Detachable Faceplate w/ Carry Case Bluetooth V2.0 Hands Free Calling From Enabled Devices A2DP Wireless MP3 Audio Playback From Enabled Devices Playback from DVD & CD of MP3 & MP4 Playback from 32GB SD/USB of MP3 & MP4 MP3 ID3 Tag Reading of MP3 Files AUX A/V Input for Personal Media Devices Front & Rear Pre-Amp Audio Outputs Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 52w x 4 MOSFET Speaker Outputs Custom & Preset Equalizer Settings Multi-Region FM Frequency Stepping 720x420 high Definition Widescreen Resolution 400 NIT Energy Efficient LED Display Backlight



PD-930B

1-DIN Multimedia Source Unit w/ Detachable 9.3" LCD Touch Screen



Motorized 9.3" LCD Touchscreen w/ Angle Adjustment Theft Deterrent Detachable Faceplate w/ Carry Case Standard & Extended Installation Sleeve & Trim Ring Included iGlass Low Glare Anti-Reflection LCD Touch Screen Technology Accepts Farenheit OEM & Steering Wheel Control Interface Bluetooth V2.0 Hands Free Calling From Enabled Devices A2DP Wireless MP3 Audio Playback From Enabled Devices Playback from DVD & CD of MP3 & MP4 Playback from 32GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track & Artist Information AUX A/V Input for Personal Media Devices 90° Angle USB & AUX A/V Input Cable Included Front & Rear Pre-Amp Audio Outputs Variable Subwoofer Pre-Amp Output Video Output for Auxiliary Devices Rear View Camera Input w/ Trigger 52w x 4 MOSFET Speaker Outputs Custom & Preset Equalizer Settings Multi-Region FM Frequency Stepping 800x480 High Definition Widescreen Resolution 400 NIT Energy Efficient LED Display Backlight

PDR-654B

2-DIN Digital Media Receiver w/ 6.5" LCD Touch Screen w/ Bluetooth



PDR-780B

1-DIN Digital Media Receiver w/ 7" Flip-Up LCD Touch Screen w/ Bluetooth



PDR-340B 1-DIN Digital Media Receiver w/ Detachable 3.4" LCD Screen w/ Bluetooth



ADDITIONAL SERIES DETAILS: Bluetooth Hands Free Calling from Enabled Phone A2DP MP3 Audio Playback from Enabled Device Accepts OEM Steering Wheel Control Interface Playback from 32GB SD/USB of MP3 & MP4 720p HD Video Playback of MP4, AVI & More

Audio Playback of MP3, AAC, AC3, & WMA Picture Viewer of JPEG, PNG & GIF ID3 Tag Reading for Track & Artist Information AUX Audio Input for Personal Media Devices 18 FM / 12 AM Station Memory 52w x 4 MOSFET Powered Speaker Level Outputs

DVD

DIGITAL MEDIA SOURCE UNITS















Bluetooth







Front & Rear Pre-Amp Audio Outputs Fixed 80Hz Subwoofer Output (ex. 340) Custom Audio Staging & EQ Controls Multi-Region FM/AM Frequency Stepping 800x480 HD Resolution 400 NIT LCD Brightness

SOURCE UNITS

DIGITAL AUDIO SOURCE UNITS

PCD-52B

2-DIN CD/MP3, AM/FM Receiver w/ SD/USB Playback w/ Bluetooth

CDAUDIO





S» Bluetooth AUX USB CHANGEABLE **ILLUMINATION**





ADDITIONAL SERIES DETAILS:

Bluetooth V2.0 Hands Free Calling from Enabled Phone A2DP MP3 Audio Playback from Enabled Device Playback from 32GB USB of MP3 & WMA Playback from CD, CDR, CDRW of MP3 & WMA AUX Audio Input for Personal Media Devices Front & Rear Pre-Amp Output 300w 4ch MOSFET Speaker Outputs Custom & Pre-Set Equalizer Settings Audio Staging Controls 12/24 Hour Digital Clock Remote Control Included Theft Detterent detachable face (1-Din Only) Faceplate Carry Case Included

PL-52B

2-DIN Digital Media Receiver w/ SD/USB Playback & AM/FM Receiver w/ Bluetooth



ADDITIONAL SERIES DETAILS:

Bluetooth V3.0 Hands Free Calling From Enabled Devices A2DP Wireless MP3 Audio Playback From Enabled Devices Playback from 32GB SD/USB of MP3 & MP4 ID3 MP3 Tag Reading for Track & Artist Information AUX Audio Input for Personal Media Devices Front & Rear Pre-Amp RCA Outputs Subwoofer Pre-Amp RCA Output 300w 4ch. MOSFET Speaker Outputs Custom & Preset Equalizer Settings Remote Control Included Theft Detterent detachable face (1-Din Only) ILLUMINATION Multi-Region FM Frequency Stepping



PL-50 Fixed Panel

PL-51B Detachable (w/Bluetooth V2.0) 1-DIN Digital Media Receiver w/ SD/USB Playback & AM/FM Receiver





Bluetooth AUX

USB

PADVD-390

1-DIN DVD Player w/32GB SD/USB Playback

Playback from DVDR/RW of MP4 & Playback from 32GB USB of MP4, & In-Dash, Floor, & Vertical Mounting Brackets Included DIN Size Trim Ring For In-Dash Mounting Included Flash Memory for Last Position Recall Remote Control & IR Repeater Included OSD On Screen Display Digital Anti-shock A/V Pre-amp Outputs, 2V Dimensions: 6.4" x 6.2" x 2"

NEW











MHL MobileLink Interface Cables

HDM-i4 ~ iPhone4, iPhone4S, iPad2, & iPad3

HDM-A2 ~ Galaxy 2 & Select 5-Pin Android Devices

HDM-A3 ~ Galaxy 3, 4, 5, & Select 11-PIN Andriod Devices

5ft interface cable unlocks 1080p video and audio playback from MHL enabled appropriate micro connector for your mobile device. Farenheit MobileLink MHL interface cables also charge your mobile device. Available for select iOS and Android devices.



PMD-112

NFW

Ceiling Mount DVD Entertainment System w/ 11.2" LCD **PT-110CM** Ceiling Mount 11.2" LCD Monitor

Interchangeable Color Skins (beige, black, grey) Color Matched Trim Rings for Sculptured Ceilings Included 45°/45° Swivel Screen for Analed Viewing Playback from DVDR/RW of 720p MP4 Playback from 32GB SD Card or USB of 720p MP4 Flash Memory for Last Position Recall Single Channel Wireless IR Transmitter (use HIR-1 or HP-11S) 8-ch FM Stereo Transmitter for OEM Integration] A/V Input for Auxiliary Sources Rear Panel RCA A/V Input for Game Console A/V Output for Multiple Component Integration Rear Panel Play/Pause Control Triggered Bright White LED Dome Light Full Function Remote Control Included NTSC / PAL Auto Selection 800 x 480 16:9 Widescreen Resolution 400 NIT Screen Brightness Dimensions: 14"w x 12.5"d x 2.5"h







PMD-104X

Ceiling Mount DVD Entertainment System w/ 10.3" LCD

10.3" High Resolution LCD Screen 1.024 x 600 16:9 Widescreen Resolution Interchangeable Color Skins (beige, black, grey) Automotive-Spec DVD Transport for Extreme Conditions Playback from DVDR/RW of MP4 & AVI Playback from 32GB SD/MMC or USB of 1080p MP4, AVI, or RCA A/V Input from Auxiliary Sources Rear Panel RCA A/V Input from Game Console Pre-Amp Audio Outputs Single Channel Wireless IR Transmitter (use HIR-1 or HP-11S) 330 Ch. FM Stereo Transmitter for OEM Integration Full Function Remote Control Included NTSC / PAL Auto Selection 400 NIT Screen Brightness Dimensions: 13"w x 11"d x 2.5"h



Transmitter

PMD-102X Ceiling Mount DVD Entertainment System w/ 10.2" LCD

Interchangeable Color Skins (beige, black, grey) 45°/270° Swivel Screen for Angled Viewing Playback from DVDR/RW of 720p MP4 Playback from 32GB USB of 720p MP4 Flash Memory for Last Position Recall FM Stereo Transmitter for OEM Integration Single Channel Wireless IR Transmitter (use HIR-1 or HP-11S) A/V Output for Multiple Component Integration A/V Inputs for Auxiliary Sources Rear Panel RCA A/V Input for Game Console Rear Panel Play/Pause Control Triggered Bright White LED Dome Light Full Function Remote Control Included NTSC / PAL Auto Selection 1.024x600 16:9 Widescreen Resolution 400 NIT Screen Brightness Dimensions: 11.5"w x 11"d x 2.5"h





PMD-90

Ceiling Mount DVD Entertainment System w/ 9" LCD NEW

> Interchangeable Color Skins (beige, black, grey) Color Matched Trim Ring for Sculptured Ceiling Included 45°/45° Swivel Screen for Analed Viewing Playback from DVDR/RW of 720p MP4 & Other Video Formats Playback from 32GB SD/USB of 720p MP4 & Other Video Formats Single Channel Wireless IR Transmitter (use HIR-1 or HP-11S) 8-ch FM Stereo Transmitter for OEM Integration A/V Input for Auxiliary Sources A/V Output for Multiple Component Integration Triggered Bright White LED Dome Light NTSC / PAL Auto Selection 800 x 480 16:9 Widescreen Resolution

400 NIT Screen Brightness Dimensions: 11"w x 9.75"d x 2.5"h









18

DVD

OVERHEAD ENTERTAINMENT











HDVD-91CC

Universal Replacement Headrest w/ DVD Player & 9" LCD

HDVD-71CC

Universal Replacement Headrest w/ DVD Player & 7" LCD

H-91CC Universal Replacement Headrest w/9" LCD

H-71CC Universal Replacement Headrest w/ 7" LCD



ADDITIONAL SERIES DETAILS:

Forward/Backwards Tilting Headrest 3 Changeable Color Skins Included (grey, beige, black) Playback from DVDR/RW of 720p MP4 (HDVD only) Playback from 32GB SD Card or USB of MP4 (HDVD only) Dual Channel Wireless IR Transmitter (use HIR-2 or HP-12S) FM Stereo Transmitter for OEM Integration (HDVD only) AUX A/V Input for Game Console or Personal Media Devices RCA A/V Input for Auxiliary Source or Opposite Headrest

RCA A/V Output to Auxiliary Source or Opposite Headrest Hardwired Headphone Output 3/8" Locking Pole w/ 1/2" & 9/16" Adapters 4.75" ~ 8.25" Pole Width Adjustment NTSC / PAL Auto Selection 800 x 480 16:9 Widescreen Resolution 400 NIT Screen Brightness Dimensions: 11.5"w x 8.5"h x 6"d (91CC) Dimensions: 10"w x 7"h x 5.5"d (71CC)

Universal Replacement Headrest Preloaded w/ DVD Player, 7" LCD, & MHL MobileLink





ADDITIONAL DETAILS:

Forward/Backwards Tilting Headrest w/ 7" LCD & DVD MobileLink Input for Mobile Device Screen Mirroring 2A Charging of Applicable Mobile Devices by USB (requires MobileLink interface cable, sold separate) 3 Changeable Color Skins Included (grey, beige, black) Playback from DVD or DVD-R of 720p MP4 & Other Formats Playback from USB of 720p MP4 & Other Video Formats AUX A/V Input for Game Console or Personal Media Devices RCA A/V Input for Auxiliary Source or Opposite Headrest

MHL MobileLink Interface Cables

HDM-i4 ~ *iPhone4*. *iPhone4S*. *iPad2*. & *iPad3* HDM-A2 ~ Galaxy 2 & Select 5-Pin Android Devices HDM-A3 ~ Galaxy 3, 4, 5, & Select 11-PIN Android Devices

5ft interface cable unlocks 1080p video and audio playback from MHL enabled appropriate micro connector for your mobile device. Farenheit MobileLink MHL interface cables also charge your mobile device. Available for select iOS and Android devices.

REAR SEAT ENTERTAINMENT

HDVD-71HD

RCA A/V Output to Auxiliary Source or Opposite Headrest Dual Channel Wireless IR Transmitter (use HIR-2 or HP-12S) Built-in FM Stereo Transmitter for OEM Integration 3.5mm Headphone Output on Front Panel 3/8" Locking Pole w/ 1/2" & 9/16" Adapters 4.375" ~ 8.25" Pole Width Adjustment Automatic NTSC & PAL Video Playback 800 x 480 16:9 Widescreen Resolution 400 NIT Screen Brightness Dimensions: 10"w x 7"h x 5.50"d





REARSEAT ENTERTAINMENT

PHAD-7

Universal Headrest Mount DVD Player w/ 7" LCD

Bracket Mount DVD Player Solution for Vehicles w/ Active Headrest Front Loading DVD Player for DVD/RW 720P Playback 32GB USB & SD Card Readers for MP4 Playback Dual Channel Wireless IR Transmitter (use HP-12S) FM Stereo Transmitter for Easy OEM Integration AUX A/V Input for Game Console or Personal Media Devices RCA A/V Input for Auxiliary Source or Opposite Headrest RCA A/V Output to Auxiliary Source or Opposite Headrest 3.5mm Hardwired Headphone Output Jack 3 Changeable Colors Skins Included (grey, beige, & black) 4.75"-8.25' Pole Width Adjustment Various Pole Diameter Adapters Included NTSC / PAL Auto Selection 800 x 480 16:9 Widescreen Resolution 400 NIT Screen Brightness



A/V USB



PT-712IRA

DVD

7" Dual Channel IR Headrest Monitor

Two Auxiliary A/V Input Dual Channel IR Transmitter Wired Headphone Output Low Refection TFT-LCD Monitor Ultra Bright LED Backlighting Selectable Aspect Modes

Preset/Manual Image Control Dimmer Control Remote Control NTSC/PAL Selection 480 x 234 (16:9) Image Resolution Cutout Dimensions: 7"w x 4.75"h x .75"d



POWER RECUSTIK

N 160 M N 160 M A / 200M O

PT-700MHR

7" LCD Headrest Monitor

7" Amorphous Active Matrix TFT/LCD Monitor Ultra Bright LED Backlighting Ianition Power On/Off Optional Single Video Input Selectable Aspect Modes Preset/Manual Image Control NTSC/PAL Selection

Sculptured Trim Ring Included Remote Control Included 480 x 234 (16:9) Image Resolution 400NIT Panel Brightness Cutout Dimension: 7"w x 4.5"h x 1"d



HP-10S Single 1ch. IR Headphone EVA hard carrying case included Foldable Ear Pads for Compact Storage On/Off Switch Saves Battery Life Auto Power Off Function Auto Mute Function Variable Volume Control ALC Auto Level Control

NEW

HP-12S Single 2ch. IR Headphone Adjustable Headphone Straps Aujustable meaupitone Suraps Channel Selectable From Each Headphone Ear Pads Fold Flat for Seat Pocket Storage EVA hard Carry Case Included MP-3 Player Input Via 3.5mm Jack On/Off Switch Saves Battery Life Auto Power Off Function Auto Mute Function Variable Volume Control ALC Auto Level Control

WLHP-100 Single 1ch. IR Headphone

WLHP-200 Single 2ch. IR Headphone Adjustable Headphone Straps Single Channel UHF IR Receiver ON/OFF Switch Saves Battery Life Variable Volume Control ALC Auto Level Control Auto Off and Auto Mute

WIRELESS HEADPHONES

Single 1ch. IR Headphone - White Single 1ch. IR Headphone - Black Single 2ch. IR Headphone - White Single 2ch. IR Headphone - Black

Single 1ch or 2ch Infrared Headphone Available in Graphite Black or Snow White Independently Swiveling Ear Cup Ear Cup Fold Flat for Convenient Storage Soft Comfortable Faux Leather Ear Pad Adjustable Headband w/ Silicone Headliner Built-in Momentary Mute Switch 25ft Maximum Operational Range

Auto Off Timer Increases Battery Life 40mm Mylar Extended Frequency Driver Variable Volume Level Control Soft Touch Cinch Carry Bag Included Requires 2 AAA Batteries (included) Ch. 1: L 2.3mHz, R 2.8mHz Ch. 2: L 3.2mHz, R 3.8mHz

HIR-1W

HIR-1B

HIR-2W

HIR-2B

HP-11S Single 1ch. IR Headphone



HP-22IRT Pair 1ch. IR Headphones and Transmitter Ear Pads Fold Flat for Seat Pocket Storage Adjustable Headphone Straps EVA hard Carry Case Included MP-3 Player Input Via 3.5mm Jack On/Off Switch Saves Battery Life Auto Power Off Function Auto Mute Function Variable Volume Control ALC Auto Level Control

HP-900S Single 2ch. 900MHz Headphone HP-9003 Single ZCII. SUUMINZ REAUPTIONE HP-902RFT Pair 2ch. 900MHz Headphones & Transmitter

Channel Selectable From Each Headphone Adjustable Headphone Straps Ear Pads Fold Flat for Seat Pocket Storage EVA hard Carry Case Included MP-3 Player Input Via 3.5mm Jack On/Off Switch Saves Battery Life Auto Power Off Function Auto Mute Function Variable Volume Control ALC Auto Level Control

REARVIEW CAMERAS

LP-2CSB

License Plate Frame w/ Night Vision Camera, Back-Up Sensors, On-Screen Distance Gauge, & Proximity Alerts

U.S. Patent #7,106,183 B2 3 Object Sensors w/ Proximity Alert 1/4" CCD Color Camera 0.5 LUX Low Light Lens Waterproof Camera Housing Waterproof External Wire Connections Vertically Pivoting Camera Housing 7' Effective Viewing Distance Inconspicuous Speaker for Alerts 8 IR LEDs for Night Viewing On-Screen Distance Gauge 130° Capture Angle RCA Video Output Cast Steel Allov Frame Reversed Image 640 x 480 Resolution



L-3CSB

License Plate Mount Night Vision Camera w/ Back-Up Sensors, On-Screen Distance Gauge, & Proximity Alerts

U.S. Patent #7,106,183 B2 2 Object Sensors w/ Proximity Alert 1/4" CCD Color Camera 0.5 LUX Low Light Lens Waterproof Camera Housing Waterproof Wire Connections Vertically Pivoting Camera Housing 7' Effective Viewing Distance

Inconspicuous Speaker for Alerts 130° Capture Angle 8 IR LEDs for Night Viewing On-Screen Distance Gauge RCA Video Output Cast Steel Alloy Reversed Image 640 x 480 Resolution



CAM-4LF

Black Chrome License Plate Frame with Camera

Zinz Alloy Metal License Plate Frame Vertically Pivoting Camera Housing On-Screen Distance Gauge 1/4" CCD Wide View Color Camera 0.1 LUX Low Light Lens 163º Capture Angle RCA Video Output Reversed Image 648 x 488 Resolution





CAM-3L

Black Chrome License Plate Trim with Camera

Zinz Alloy Metal License Plate Trim Vertically Pivoting Camera Housing On-Screen Distance Gauge 1/4" CCD Wide View Color Camera 0.1 LUX Low Light Lens 163° Capture Angle RCA Video Output Reversed Image 648 x 488 Resolution





CAM-2 1" Surface Mount Rear View Camera

Vertically Pivoting Mounting Bracket Waterproof Zinc Camera Housing On-Screen Distance Gauge 1/4" CCD Color Camera 0.1 Lux Low Light Lens 163º Capture Angle RCA Video Outputs Reversed Image 648 x 488 Resolution



Waterproof Zinc Camera Housing On-Screen Distance Gauge 1/4" CCD Color Camera 0.1 Lux Low Light Lens 163º Capture Angle RCA Video Outputs Reversed Image 648 x 488 Resolution

CAM-1

CCD-6XS Water-Proof Surface Mount Rear View Camera

1/3" CCD GHigh Definition Color Camera by PixelPlus IP67 Waterproof Nickel Plated Zinc Alloy Housing Threaded Mounting System for Easy DIY Installation Vertical Image Inversion for Front/Rear Application Optional On-Screen Distance Gauges Rear View Image Pre-Reversed RCA Video Output 163° Viewing Angle 0.1 LUX Low Light Lens 682x496 Resolution



EFM-02 PLL FM Modulator

PLL Phase Lock Loop Tuner Outputs Frequency Settings Via Slide Switch Ground Loop Isolator Circuit Shielded Metal Housing For Noise Rejection





1" Under Trunk Lid Rear View Camera



CCD-4XS 1" Surface Mount Rear View Camera

Vertically Pivoting Mounting Bracket Waterproof Camera Housing On-Screen Distance Gauge 1/4" CCD Color Camera 0.1 Lux Low Light Lens 163º Capture Angle RCA Video Outputs Reversed Image 648 x 488 Resolution



CCD-1 Water-Proof Surface Mount Rear View Camera

Vertically Pivoting Stand for Angled Installation Waterproof Camera Housing 8 IR LEDs for Night Viewing 1/3" Sharp CCD Color Camera 0.1 LUX Low Light Lens RCA Video Output Reversed Image 512 x 582 Resolution





VB-1 One In & Four Output Video Signal Booster

Four Individual Output Trimmer Gain Controls Shielded Metal Housing For Noise Rejection 4 Video Output Gain control



MAKE YOURSELF HEARD!

NEW

Class A/B Full Range & Class D Monoblock Amplifiers Die-Cast Aluminum Alloy Heatsink for Optimum Dissipation 2-ohm Stereo & 4-ohm Bridged Full Range Operation 1-ohm Stable Monoblock Operation for MAX Power Bridge 2 Monoblocks Together for Double Power! MOSFET Power Supply w/ Audiophile Grade IR™ Transistors Military Grade SMT PCB Maintains Dynamic Performance Direct Short, Thermal, & Overload Circuits Protect Ampllifier Easy DIY Install Single Sided Terminals & Controls Angled Wire Terminals Secure Wire Connections Chassis Integrated Aluminum Mounting Points Variable 12dB High Pass, Low Pass, & Subsonic Crossovers 200mV-6V Low Level RCA Inputs 4g Power Wire & 8g Speaker Wire Outputs 12dB Bass Boost Increases Low Octave Harmonics 180^o Phase Shift Improves Low Octave Dynamics (monoblock) Dash Mount Gain Control Module Included (select models)

Class A/B	Max Power	RMS Power	RMS Power	RMS Power	Dimensions	Gain Control	
Full Range	(watts)	4Ω Bridged, 14.4V	2Ω, 14.4V	4Ω, 14.4V	(2.25"h x 8.5"w)	Included	
BAMF4-1200	1,200w	2 x 300	4 x 150	4 x 75	11.25"	-	
BAMF4-1800	1,800w	2 x 450	4 x 225	4 x 110	13.25"	-	<
BAMF5-2500	2,500w	2 x 200+ 1 x 850 (2Ω)	4 x 100 + 1 x 850	4 x 50 + 1 x 425	17"	Included	
BAMF1-3000D	3,000w	1 x 1,500 (1Ω)	1 x 1,000	1 x 700	11.25"	Included	
BAMF1-5000D	5,000w	1 x 2,500 (1Ω)	1 x 1,700	1 x 1,100	13.25"	Included	
BAMF1-8000D	8,000w	1 x 4,000 (1Ω)	1 x 2,700	1 x 1,800	17"	Included	



BDGE AMPLIFIERS

the edges bring a high end appeal to traditional performance.

NEW

Class A/B Full Range & Class D Monoblock Amplifiers

Class Avo Full Mange & Class D Wolfson Chipmens 2-ohm Stereo & 4-ohm Bridged Full Range Operation

2-orini Steley & 4-orini Diviged Full Narige Operation 1-ohm Stable Monoblock Operation for MAX Power

Direct Short, Thermal, & Overload Circuit Protection High/Speaker Level & Low Level/RCA Input

(watts)

1.400W

1,000W

1,500w

2,800W

2,500W

4,500W

7,000W

10,000W

Bridge 2 Monoblocks Together for Double Power! Military Grade PCB W/ PWM MOSFET Power Supply

200mV-6V Low Level RCA Input

Edg

Amplifie

EG2-1400

EG4-1000

EG4-1500

30

EG5-2800

EG1-2500D

EG1-4500D

EG1-7000D

EG1-10000D

New for 2016, Edge amplifiers are the next step in performance and value. Taking advantage of our tried and true class A/R full range and improved efficiency class d monoblock platforms. Edge amplifiers continue down New for 2016, Edge amplitiers are the next step in performance and value. Taking advantage of our tried and true class A/B full range and improved efficiency class d monoblock platforms, Edge amplifiers continue down the road of reliability and longevity you know well. Satin silver chassis, engraving, and accents teetering on true class A/B full range and improved efficiency class d monoblock platforms, Edge amplifiers continue down the road of reliability and longevity you know well. Satin silver chassis, engraving, and accents teetering on the edges bring a high end appeal to traditional performance.

POWER REDUSTIK

Pre-Amp Low-Level RCA Outputs (select models)

4g Power Wire & 8g Speaker Wire Outputs

(2.25"h x 9"w)

12.75"

10.25"

12.75"

19.75"

10"

13

16.25"

20.5

4Ω, 14.4V

2 x 175

4 x 65

4 x 95

4x80+1x380

400 x 1

750 x 1

1.100 × 1

1,600 x 1 (2Ω)

RMS PO

RMS POV

4Ω Bridged, 14.4V

1 x 700

2 x 250

2 x 370

2 x 320 + 1 x 760 2Ω

1,250 x 1 (1Ω)

2,250 x 1 (1Ω)

3,500 x 1 (1Ω)

5,000 x 1 (0.5Ω)

2Ω, 14.4V

2 x 350

4 x 125

4 x 185

4 x 160 + 1 x 760

800 x 1

1,500 x 1

2,300 × 1

3,300 x 1 (1Ω)

Variable 12dB High & Low Pass Crossovers 12dB Bass Boost Increases Low Octave Harmonics 1206 Bass Boost Increases Low Octave Mannonics (monoblock) 180º Phase Shift Improves Low Octave Dynamics (monoblock)

Dash Mount Remote Control Included (select models)

Included

Included

Included

Included

Included

Dash Mount Gain

Control Included

RAZD

We're in a time where small is "in". Smaller, more economic vehicles are more and more desirable. But that doesn't mean you have to sacrifice hid power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient Full-Range Class D We're in a time where small is "in". Smaller, more economic vehicles are more and more desirable. But that doesn't mean you have to sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient Full-Range Class provide the sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient full-Range Class provide the sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient full-Range Class provide the sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient full-Range Class provide the sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient full-Range Class provide the sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient full-Range Class provide the sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient full-Range Class provide the sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient full-Range Class provide the sacrifice big power and SMT efficient full-Range for your possible preamp adjustment the Razor amplifiers leave nothing to be desired to power the sacrifice big power and sacrifice big power to sacrifice big power for your system. Razor amplifiers pack huge power into small chassis thanks to efficient Full-Range Class D topology and SMT circuitry. Complimented with every possible preamp adjustment, the Razor amplifiers leave nothing to be desired... Newest additions include a 3,000w 4ch model, and a 1-ohm stable 3,500w monoblock...

Compact 4.75" Chassis Design for Installation Versatility MOSFET Power Supply w/ Audiophile Grade IRTM Transistors Military Grade SMT PCB Maintains Dynamic Performance 2-ohm Stereo & 4-ohm Bridged Full Range Operation

Direct Short, Thermal, & Overload Circuits Protect Ampllifier

Variable 1200 FIGUR Fass & LOW Fass Crossover Protects Subwoofers 10-50Hz Variable 12dB Subsonic Crossover Protects Subwoofers

12dB Bass Boost Increases Low Octave Harmonics (monoblocks)

Max Power

(watts)

1,300

1,200

2,000

3,000

2,500

1,500

2,300

3,500

4Ω Bridged

Dash Mount Gain Control Module Included (select models)

RAZOR

RZ2-1300D

RZ4-1200D

RZ4-2000D

RZ4-3000D

RZ5-2500D

RZ1-1500D

RZ1-2300D

RZ1-3500D

CLASS D

2-ohm Minimum Impedance Stablity (monoblocks)

High Level Input w/ Signal Sense Auto Turn-on

200mv-6V Low Level RCA Inputs

RAD RAMPLIFIERS

POWER ACOUSTH



Dash Mount Gain Control Included

Installs in Virtually ANY Location! 90% Efficient Full Range Class D Technology



oblocks)				Gain Control	
		- Dower	Dimensions (4.75"w x 1.625"h)	Deduded	
	RMS Power	RMS Power 4Ω, 14.4V	(4.75"W X 1.021 5.5"	Inciudou -	
RMS Power	20 14.4V	2 x 185	9"	•	
Bridged, 14.4*	2 x 270	4 x 100	11"	-	
1 x 540	4 x 150	4 x 190	12.25"	Included	
2 x 300	4 x 250	4 x 285	12.25	Included	
2 x 500	4 × 375	$1 + 400 \times 1$	10"	Included	
o x 750	$-0 \times 4 + 600 \times 10^{-10}$	1 x 600	11"	Included	
300 x 2 + 600 x 1	1 x 900	1 x 900	12.25"		
-	1 x 1,400	1 x 900			
-	1 x 1,400				
1 x 2,100					





717



Dash Mount Gain Control Included (monoblock)

	RMS Power	Dimensions (5"w x 2"h)	Remote Gain Included
ower	4Ω, 14.4V	8"	Included
.4V	4 x 100	8"	
150	1 x 400		
600			



MOFO X subwoofers are refined and increase efficiency dramatically! MOFO-X subs use a composite sandwich cone with a polypropylene surface for durability and Spruce pulp backing for smooth low bass. Like the original MOFOs, the new models still use an aluminum dustcap that couples to the voice coil former and extends over the cone. Why? The fins brace the cone and eliminate cone flex during high excursion. And since they are aluminum and couple to the voice coil, they act as a heatsink or heat extractor. Using the latest materials, the new MOFO subs yield superior performance. Cast aluminum baskets? Of course! Increased bottom octave output? You Bet! Louder than the original design? Duh!!

((((0-........))))

Pre-Assembeld Re-cone Kit Available

Overcompensating Motor Sturcture for Increased Magnetic Strength 12mm T-Yoke & Top Plate Improve Low Frequency Dynamics Vented T-Yoke & Frame Reduces Voice Coil Heat Build-up Die Cast Aluminum Heatsink Dust Cap Absorbs Voice Coil Heat Aluminum Dust Cap Fins Dissipate Heat & Strengthen Cone Non-Magnetic Non-Resonate Die-Cast Aluminum Frame 2.5" 4-Layer Voice Coil w/ Large Gauge Wire Increases Power Handling High-Temperature Tollerance Adhesives Resist Thermal Failure Nickel Plated 8ga Spring-Loaed Compression Wire Terminals Non-Transfer Spruce Pulp Cone w/ UV & Chemical Protection High Density Polyether Foam Surround w/ UV & Chemical Protection Dual Poly-Cotton Suspension Dampen Violent Accelerations Stitched Voice Coil Leads Prevent Potential Damage 1-pc Gasket/Trim Ring w/ Concealed Mounting Holes Included

MOFO Max Power **RMS Power** Efficiency Motor Mounting **Optimum Ported** Voice Coi **Optimum Sealed** Handling Configuration Volume Enclosure ft³ Enclosure ft³ Subwoofers Handling (1w/1m)Depth MOFO-122X 2,700 1.500 85.37 2.50" Dual 2Ω 373oz. 6.875' 1.00 2.00 MOFO-124X 2,700 1,500 85.40 2.50" Dual 4Ω 373oz 6.875' 1.00 2.00 MOFO-152X 3.000 1.700 86.90 2.50" Dual 2Ω 373oz 8.125" 2.00 4.00 MOFO-154X 3,000 1.700 86.97 2.50" Dual 4Ω 373oz. 8.125" 2.00 4.00



BAMF subwoofers are the newest secret weapon for you bass BURP fanatics! These beasts are engineered for the most extreme conditions. Massive 3" 4-layer voice coils built on an aluminum former can take the heat. Freakishly oversized motor structures provide more magnetic inertia than is ever necessary for a woofer. Spruce tree pulp cones, high densitiv extended exursion foam surround, and hybrid suspension dampers work together to contain the momentum to a shattering roar...

Overcompensating Motor Sturcture for Increased Magnetic Strength 12mm T-Yoke & Top Plate Improve Low Frequency Dynamics Vented T-Yoke & Frame Reduces Voice Coil Heat Build-up Non-Magnetic Non-Resonate Die-Cast Aluminum Frame 3" 4-Layer Voice Coil w/ Direct Connect Wire Increases Power Handling High-Temperature Tollerance Adhesives Resist Thermal Failure

BAMF	Max Power	RMS Power	Efficiency	Voice Coil	Motor	Mounting	Optimum Sealed	Optimum Portec
Subwoofers	Handling	Handling	(1w/1m)	Configuration	Volume	Depth	Enclosure ft ³	Enclosure ft ³
BAMF-122	3,500w	1,750w	81.30	3" Dual 2Ω	204oz.	6.00"	1.50	2.50
BAMF-152	3,800w	1,900w	83.60	3" Dual 2Ω	254oz.	6.50"	2.50	3.50

Non-Transfer Spruce Pulp Cone w/ UV & Chemical Protection Sitched and Glued Surround/Cone Joints for Strongest Bonding Extended Excursion Polyether Foam Surround w/ UV Protection Dual Poly-Cotton Suspension Dampen Violent Accelerations Stitched Voice Coil Leads Prevent Potential Damage 1-pc Gasket/Trim Ring w/ Concealed Mounting Holes Included

OTHIC GUENOOFER

Twisted & Woven Flax Fiber Cone

All Gothic woofers use torsion twisted Flax fibers woven together for ultimate strength and less elasticity. A heavy soaking in epoxy combined with the sonic qualities of pulp paper, Flax proves itself worthy of any system.

Extended Excursion NBR Surround

A strong and flexible heat resistant compound, nitrile butadiene rubber is used widely in automotive applications. Gothic woofers utalize an extended excursion NBR surround for it's strength and flexible properities during extreme movement.

Back Plate & T-Yoke Venting

Heat build-up is a leading cause of catastrophic woofer failure. Venting built into the T-Yoke, back plate, and voice coil extract and dissapate heat, ensuring Gothic woofers keep their cool.

Overcast Stitched Cone Assembly

Surrounds of Gothic woofers are double overcast stitched directly to the Flax cone surface. In addition to superior adhesives, overcast stitching improves the conventional bond between cone and surround.

100% OFC 4-Layer Voice Coil

Gothic woofers use generous 1.50" long, 2.5" diameter 100% OFC Copper voice coils. A vented Aluminum former extract and dissapate any heat build-up, resulting in improved power handling.

Gothic	Max Power	RMS Power	Efficiency	Voice Coil	Motor	Mounting	Optimum Sealed	Optimum Ported
Subwoofers	Handling	Handling	(1w/1m)	Configuration	Volume	Depth	Enclosure ft ³	Enclosure ft ³
GW3-10	2,200	1,000	81.30	2.50" Dual 2Ω	204oz.	6.00"	1.00	1.50
GW3-12	2,500	1,200	83.60	2.50" Dual 2Ω	254oz.	6.50"	1.50	2.25
GW3-15	3,000	1,400	84.00	2.50" Dual 2Ω	254oz.	7.50"	2.75	3.25



An addition to the THIN family, this shallow mount 12" subwoofer yields the performance of most conventional 12" subwoofers, but needs only 3" for mounting. Consider THIN-124 optimum for pre-fab under seat and behind rear seat shallow enclosures.

Spruce Paper Cone for Dynamic, Natural Sound Quality Semi-Circular Frame Venting Maintains Thermal Control Internal Motor Assembly Reduces Mounting Depth 3" Mounting Depth to Install in Any Vehicle Type 2" 4-ohm DVC for Multiple Woofer Application

CILLIER FICOL

THIN-124	Max Power	RMS Power	Efficiency	Voice Coil	Motor	Mounting	Optimum Sealed	Optimum Ported
Subwoofer	Handling	Handling	(1w/1m)	Configuration	Volume	Depth	Enclosure ft ³	Enclosure ft ³
THIN-124	2,000	850	86dB	2.00" Dual 4Ω	104oz.	3.00"	1.00	2.00

Cryptquewoor

Injection Molded Polypropylene Cone Overcast Stitched Cone Assembly Closed Cell Polyurthane Foam Surround 100% OFC 4-Layer Voice Coil Back Plate & T-Yoke Venting Embossed Dust Cap

Crypt	Max Power	RMS Power	Efficiency	Voice Coil	Motor	Mounting	Optimum Sealed	Optimum Ported
Subwoofers	Handling	Handling	(1w/1m)	Configuration	Volume	Depth	Enclosure ft ³	Enclosure ft ³
CW2-104	1,800	720	88.40	2.00" Dual 4Ω	162oz.	5.875"	1.00	1.50
CW2-124	2,000	850	89.90	2.00" Dual 4Ω	190oz	6.375"	1.25	1.75
CW2-154	2,200	1,000	88.90	2.00" Dual 4Ω	190oz	7.25"	2.50	3.00

THIN-120BXA Powered Enclosure

Pre-loaded Enclosure w/ 12" Subwoofer 4 Ohm Impedance 650W Built in Amp Carpeted Black w/ Embroidered Accents 29.75" I x 14.5" h x 5.75"/2.25" d



14




Power ACOUSTIK

THIN-8A Preloaded Enclosure

Pre-loaded Active Enclosure w/ 8" Subwoofer 500w MAX Monoblock Amplifier Built-In Cast Aluminum Chassis Hi-Speaker Level Inputs 200mV-6V Low Level RCA Input Variable 2dB Low Pass Crossover 1800 Phase Inversion Switch Dash Mount Gain Control Included 3"h x 9.5"w x 13.5"L







GF-653

1" Kapton Voice Coil Reinforced Cloth Surround 2" Paper Cone Midrange 2° Paper Corre Michaelge Balanced Dome Tweeter 6dB In-Line Crossover

High Efficiency PP Coated Paper Cone

GF-60C

10

High Efficiency PP Coated Paper Cone 1" Kapton Voice Coil Reinforced Cloth Surround 1" Swivel Dome Tweeter Flush or Surface Mounting 12dB In-Line Crossover Included

0

PTC Tweeter Protection

Gothic

Speakers

GF-60C

GF-693

GF-653

GF-693

Frequency

Response

75-20kHz

65-20kHz

75*20kHz

MAX

Power

350W

500W

350W

Size &

туре

6.5" Component

6"x9" 3-way

6.5" 3-way

Efficiency

(1w/1m dB)

91dB

93dB

91dB

Mounting

Depth

2.125"

2.875"

2.125"

FF-653

Improved Efficiency Diaphragm & Magnet Structure Carbon Fiber Injection Molded Polypropylene Cone Edge Treated Woven Cloth Surround 1" Voice Coil on Aluminum Former Speakers 1" Voice Coil on Aluminum Former 4-ohm System Impedance Quick Disconnect Terminals 2" Balanced Dome Mylar Midrange (EF-694) 1" Balanced Dome Mylar Tweeter 1/2" Dome Super Tweeter (select models) EC-60C EF-694 EF-573 EF-653 EF-52 EF-42

EF-

52		Frequency	Efficiency (1w/1m dB)	Mounting Depth 1.75"
Size &	MAX Power	Response 65-20kHz	92dB	3.25"
Type	500W	65-20kHz 45-20kHz	93dB 92dB	1.75" 1.75"
6.5" Component	800w	65-20kHz	92dB	2.125"
6"x9" 4-way 5" x 7" 3-way	500w 400w	65-20kHz 80-20kHz	90dB	1.75"
6.5" 3-way	300W	80-20kHz	90dB	
5.25" 2-way 4" 2-way	250w			



NX-3 Horn Tweeter 200 Watts MAX

1.75" Aluminum Dome Diaphrgam Phase Inversion Plug 6dB Crossover Capacitor Included Freq. Resp 3kHz – 20KHz 4-Ohm Impednace Efficiency: 106dB (NX-4) Efficiency: 109dB (NX-3) Sold Individually

PRO-104

Et.

PRO-6	54				Mounting
			Frequency	Efficiency (1w/1m dB)	Depth 2.75"
	MAX	Impedance	Response	96dB	3.25"
Size &	Power	4Ω	150-15kHz 1202-8kHz	98dB 96dB	2.75" 3.25"
Туре 6.5"	300W	4Ω	150-10kHz	90dB 97dB	3.25 4.25"
0.0 8"	350w 170w	4Ω 10	120-8kHz	98dB	
6.5"	200W	4Ω 4Ω	100-5kHz		
8"	350W				

PRO-804

EQUALIZERS

10



BASSBOX-8

Chrome Finish w/ Illuminated Badge PWM High Head Room Power Supply 27-63Hz Parametric Bass Boost Variable Bandwidth Adjustment Max Output Level: 13.5 volt Dash Mount Remote Control LED MAX Bass Indicators 35-80Hz Variable Subsonic Filter Balanced RCA Inputs Selectable Input Ground Sources Selectable Grounding Isolation Frequency Response: 10~100kHz THD: 0.003% S/N Ratio: 130dB

BASS-10C Bass Maximizer

PWM High Head Room Power Supply 27-63Hz Parametric Bass Boost Variable Bandwidth Adjustment Max Output Level: 13.5 volt Dash Mount Remote Control LED MAX Bass Indicators Selectable Subsonic Filter Balanced RCA Inputs Selectable Input Ground Sources Selectable Grounding Isolation Frequency Response: 10~100kHz THD: 0.003% S/N Ratio: 130dB Input Noise Rejection: 60 dB

BASS-12C Bass Maximizer

Chrome Finish w/ Illuminated Badge PWM High Head Room Power Supply 27-63Hz Parametric Bass Boost Variable Bandwidth Adjustment Max Output Level: 13.5 volt Dash Mount Remote Control LED MAX Bass Indicators 35-80Hz Variable Subsonic Filter Balanced RCA Inputs Selectable Input Ground Sources Selectable Grounding Isolation Frequency Response: 10~100kHz THD: 0.003% S/N Ratio: 130dB

PWM-70 7-Band 1/2 DIN Equalizer

2 Selectable Balanced Inputs Selectable Input Sensitivity 7 bands +/- 18dB Parametric Equalizer Independent Volume & Fader Control Independent Subwoofer Output and Level Control Selectable Subwoofer Low-Pass Crossover 8V MAX Front, Rear, & Subwoofer Outputs Low Noise BI-FET Op-Amp for Minimum Distortion 20dB Headroom, 30V Bipolar Power Supply Blue LED Backlighting S/N Ratio 110dB @1V THD:0.05%

PWM-20 4-Band 1/2 DIN Equalizer

2 Selectable Balanced Inputs Variable Stereo Input Sensitivity 4 Variable Frequency Bands +/- 18dB Parametric Equalizer Independent Volume & Fader Control Independent Subwoofer Output and Level Control Variable Subwoofer Low-Pass Crossover 8V MAX Front, Rear, & Subwoofer Outputs Low Noise BI-FET Op-Amp for Minimum Distortion 20dB Headroom, 30V Bipolar Power Supply Blue LED Backlighting Quick Disconnect Wire Harness S/N Ratio 115dB @1V THD:0.05%

PWM-19 4-Band 1/2 DIN Equalizer

2 Selectable Balanced Inputs Variable Stereo Input Sensitivity 4 bands +/- 18dB Parametric Equalizer Independent Volume & Fader Control Independent Subwoofer Output and Level Control Variable Subwoofer Low-Pass Crossover 7V MAX Front, Rear, & Subwoofer Outputs Low Noise BI-FET Op-Amp for Minimum Distortion 20dB Headroom, 30V Bipolar Power Supply Selectable Green/Amber Illumination Quick Disconnect Wire Harness Under Dash Mounting Hardware Included S/N Ratio 110dB @5V THD:0.05%

PWM-16 4-Band 1/2 DIN Equalizer

2 Selectable Balanced Inputs & Front Panel AUX Input 4 bands +/- 18dB Parametric Equalizer Independent Volume & Fader Control Independent Subwoofer Output and Level Control Variable Subwoofer Low-Pass Crossover 7V MAX Front, Rear, & Subwoofer Outputs Blue LED Backlighting Quick Disconnect Wire Harness S/N Ratio 80dB @5V THD:0.05%





PW

BASSBOX-6

PWM High Head Room Power Supply 27-63Hz Parametric Bass Boost Variable Bandwidth Adjustment Max Output Level: 13.5 volt Dash Mount Remote Control LED MAX Bass Indicators Selectable Subsonic Filter Balanced RCA Inputs Selectable Input Ground Sources Selectable Grounding Isolation Frequency Response: 10~100kHz THD: 0.003% S/N Ratio: 130dB Input Noise Rejection: 60 dB

C-30XR 3-Way 12dB Electronic Crossover

6-Channel Low-Level Input 6-Channel Low-Level Output w/ 5V Gain 2/4 Channel Input Selection Independent Front/Rear High Pass Independent Subwoofer Low Pass Stereo or Mono Subwoofer Output Selection 180° Phase Switch Variable Frequency & Gain Bass Boost Dash Mount Remote Subwoofer Gain Module S/N Ratio: 95dB Channel Separation: 60dB

E C C C

INSTALLATION ACCESSORIES

Amplifier Wire Kits

AK-0 0g Amplifier Wire Kit w/ 200A ANL Fuse **AK-4** 4ga Amplifier Wire Kit w/ 120A MANL Fuse AK-8 8ga Amplifier Wire Kit w/ 80A MANL Fuse

Each Wire Kit Includes:

17ft Power Wire w/ Ring Terminal 3ft Ground Wire w/ Ring Terminal 17ft Twisted Pair RCA Interconnect 17ft Remote Turn-on Wire 25ft 16g Split Speaker Wire Full Size MANL Fuse Holder ANL or MANL Fuse Included Assorted Installation Accessories

Capacitors

PC1.5F

1.5 Farad Power Capacitor

Terminal Post for Ring Terminal Digital Voltage Meter Translucent Mounting Brackets rushed Aluminum Finish

PCX-3F 3 Farad Power Capacitor **PCX-5F** 5 Farad Power Capacitor

12-16 DC Volts Operation Terminal Post for Ring Terminal Digital Voltage Meter Polarity & Voltage Protection Protection Alert Indicator LED Accent Lighting Satin Finish w/ Chrome Accents



PC2.0F 2 Farad Power Capacitor



12-16 DC Volts Operation Terminal Post for Ring Terminal Digital Voltage Meter Translucent Mounting Brackets Chrome Plated Finish

PCX-30F 30 Farad Hybrid Power Capacitor

12-16 DC Volts Operation Internally Stacked Carbon-Foil Capacitors Direct Connect 0 ga. Terminals & 4 ga. Reducers Digital Voltage Meter Polarity & Voltage Protection Protection Alert Indicator LED Accent Lighting Satin Finish w/ Chrome Accents

MCD-41B (w/ Bluetooth V2.0) 1-DIN Marine CD Player w/32GB USB Playback CD/MP3, AM/FM & USB Receiver Conformal Coated PCB and Faceplate Theft Deterrent Detachable Faceplate Bluetooth V2.0 Hands Free Calling from Smart Phone Bluetooth V2.0 Hands Free Calling from Smart Phone A2DP MP3 Audio Playback from Enabled Device Playback from 32GB USB of MP3 & WMA Aux Audio Input for Personal Media Devices Font & Rear Pre-Amp Output Stat MOSFET Speaker Outputs Custom & Pre-Set Equalizer Settings Audio Staging Controls 12/24 Hour Digital Clock Remote Control Included Faceplate Carry Case Included





RAZOR CLASS D MA4-3000D MA5-2500D	Max Power (watts) 3,000	RMS Power 4Ω Bridged, 14.4V	RMS Power			
MA1-2300D MA1-3500D	2.500	2 x 750 300 x 2 + 600 x 4	252, 14.4v 4 x 375 150 x 4 + 600 x 1 1 x 1,400	$100 \times 4 + 400 \times 1$	Dimensions (4.75"w x 1.625"h) 12.25"	included
			1 x 1,400	1 x 900 1 x 900	12.25" 11" 12.25"	Included Included Included

USB * Bluetooth AUX X300 INPUT 4CH- MATLER

MARINE AMPLIFIER

Compact 4.75" Chassis Design for Installation Versatility Splash Resistant Conformal Coated Circuit Boards MOSFET Power Supply w/ Audiophile Grade IR™ Transistors Military Grade SMT PCB Maintains Dynamic Performance 2-ohm Stereo & 4-ohm Bridged Full Range Operation 2-Ohm Stable Class A/B Monoblock Operation 1-ohm Stable Class D Monoblock Operation Direct Short, Thermal, & Overload Circuits Protect Ampliifier High Level Input w/ Signal Sense Auto Turn-on Variable 12dB High Pass & Low Pass Crossovers Variable 12dB Filgh Fass & Low Pass Crossovers 10-50Hz Variable 12dB Subsonic Crossover Protects Subwoofers 12dB Bass Boost Increases Low Octave Harmonics (monoblocks) Dash Mount Gain Control Module Included (select models)

100% Waterproof Enclosure and Speaker System High Density ABS Construction w/ UV Coating Steel reinforced Mounting Bracket fits most towers Braided Stainless Steel Safety Cable Included Stainless Steel Mounting Hardware Included Polypropylene speaker cone and Titanium Tweeter Quick Disconnect Compression Terminals Meets ROHS and CE Certifications

0

Wake Tower Speakers	Size &	МАХ			System	Impedance
MWT-65W MWT-65T MWT-80W MWT-80T	Color 6.5" White 6.5" Titanium 8" White 8" Titanium	MAX Power 500w 500w 750w 750w	RMS Power 250w 250w 375w 375w	Frequency Response 40-20kHz 40-20kHz 30-20kHz 30-20kHz	Criticiency (1w/1m dB) 90dB 90dB 91dB 91dB	Overall Size (HxWxL) 8.5" x 8.5" x 9" 8.5" x 8.5" x 9" 10" x 10" x 9.5" 10" x 10" x 9.5"

MARINE WATERPROOF SPEAKERS Speakers

MF-65WT

RMS Frequency Efficiency Power 300w nse (1w/1m dB) **Overall Size** 150w 60-20kHz (WxHxL) Marine Grade Waterproof 6.5" Coaxial Speaker 7.5" x 7.5" x 2.5"

1/11/11

High Density ABS Construction w/ UV Coating 100% Waterproof Sealed Back Speaker Frame Stainless Steel Mounting Hardware Included Injection Molded Polypropylene speaker cone Rubber Surround & Tweeter Pole Gasket ¹" Titanium Dome Tweeter White and Titanium Grils Included Quick Disconnect Terminals Meets ROHS and CE Certifications 4-ohm System Impedance

1.4. F



MARINE WATERPROOF SUBWOOFER

Marine					u vv li i i f f r	
Subwoofer	ΜΑΧ	RMS			o w u u FER	ł
MW-10WT	Power		Frequency			
10001	600 _W	Power	Response	Efficiency	0	
		300w	30-4kHz	(1w/1m dB)	Overall Size	
Λ.α.			TAR			
Mar	ine Grad	dalu			10.5" x 10 5"	
Hiah	Don	ue Wate	Proof 10	91dB Subwoofer V/ UV Coati	10 X 0"	
1000	Density	ABS CO	1.001 10" (Subwoofer		
100%	Waterp	100f c	^{istruction} v	V/IIV o		
Stainle	ess stor	, ooi sea	led Back o	" UV Coati	ina	
IMPP r		ⁱ Mounti	na u	Subwoofer W/UV Coati Deaker Fran Ire Included Der Surroun	20	
	^{-oly} prop	Vleno o	"9 Hardwa	Ire Inclui	ne	
vvnite a	and Tita	Sicile C	one & Rub	s included	b	
Quick r	Die-	^{niu} m Gri	Is Inclus	^{Der} Surroun	d	
Moot	JISCONNE	nium Gri PCt Term	^{One} & Rubi ^{Is Included}		Q	
ineels R	20 Lic	Cill	mak			
4-ohm s	Vetor	u CE Ce	rtificatio			
4-ohm s	n In	npedan	Sations			
		~ Gri(-6			

AUTOMOTIVE Accessories

WINDOW FILM TINT

Automotive and Commercial Application Window Tint

Our window film uses infused color chips and twin UV inhibitors in the initial manufacturing process. This insures maximum benefit for your interior. Traditional manufacturing process uses clear chips and adds dyes, pigments, or spray-on colors, and a UV inhibitor in the adhesive.

Additional Benefits

Color-stable film that never bubbles, peels, or turns purple over time Malleable for seamless attachment to curved surfaces American made adhesives for impervious seal and undistorted views Reduces heat, glare and overall energy costs when used in home or auto Eliminate harmful UV by 99% to protect interior materials in home or auto Lifetime Warranty with Everlast Series, Made in U.S.A. 4-Year Prorated Warranty with Elite Series Available in 20", 24", 36", 40" Width, all in 100ft. length Everlast Series Available in 60" Width

Everlast Series	Elite Series
EV-05 6% VLT EV-15 16% VLT EV-20 21% VLT EV-35 35% VLT EV-50 51% VLT	LT-05 6% VLT LT-20 22% VLT LT-35 33% VLT LT-50 51% VLT

Farrentien

