

Tarantula SUBWOOFERS

REFERENCE SUBWOOFERS



TARANTULA T5	T5.102	T5.104	T5.124	T5.154
MAX Power (watts)	1,800w	2,000w	2,600w	
RMS Power (watts)	900w	1,000w	1,300w	
Efficiency (1w/1m dB)	83.5dB	86dB	88dB	
Voice Coil Configuration	3" DVC 2Ω	3" DVC 4Ω	3" DVC 4Ω	3" DVC 4Ω
Mounting Depth	6.25"	7.25"	9.25"	
Optimum Sealed Box	0.75ft ³	1.50ft ³	2.00ft ³	
Optimum Ported Box	1.25ft ³	2.50ft ³	4.00ft ³	

REFERENCE R1	R.122	R.124
MAX Power (watts)		2,000w
RMS Power (watts)		1,000w
Efficiency (1w/1m)		85.00dB
Voice Coil Configuration	2.50" DVC 2Ω	2.50" DVC 4Ω
Mounting Depth		7.00"
Optimum Sealed ft ³		1.00ft ³
Optimum Ported ft ³		2.00ft ³

Picasso SHALLOW SUBWOOFERS



PICASSO SUBWOOFERS	PSW.104	PSW.124
MAX Power (watts)	500w	600w
RMS Power (watts)	250w	300w
Efficiency (1w/1m)	86.40dB	88.41dB
Voice Coil Configuration	2" SVC 4Ω	
Mounting Depth	3.00"	3.50"
Optimum Sealed ft ³	0.75ft ³	1.00ft ³
Optimum Ported ft ³		

PSB.10A
Powered Enclosure w/ PSW-10
15h x 21.75l x 5.7"/7" (d1/d2)

PSB-12A
Powered Enclosure w/ PSW-12
15.25" h x 24" l x 5.25"/7.25" (d1/d2)

TWS.7 1" PEI Dome Tweeter

Ferrofluid cooled
Neodymium magnet
Tri-Mounting - flush, surface or angle
12dB/Octave passive crossover included
Rated Input Power: 110W
Impedance: 4ohm
Freq. Resp. 3KHz - 20KHz
SPL 93dB



PROAUDIO Components.



SM PRO Series Speakers	SM.650PRO	SM.650PROC	SM.800PRO
Size	6.5"		8"
MAX Power Handling	250w		400w
RMS Power Handling	125w		200w
Impedance	4-Ohm		4-Ohm
Frequency Response	150-10kHz	150-25kHz	150-10kHz
Efficiency (1w/1m)	94dB	96dB	97dB
Mounting Depth	3.00"		3.50"

SM Series Speakers	SME.650	SME.650C	SME.800	SM2.650	SM2.800
Size	6.5"		8"	6.5"	8"
MAX Power Handling	200w		250w	250w	400w
RMS Power Handling	100w		125w	125w	200w
Impedance	4-Ohm		4-Ohm	4-Ohm	4-Ohm
Frequency Response	150-10kHz	150-25kHz	100-10kHz	150-25kHz	100-25kHz
Efficiency (1w/1m)	91dB	93dB	94dB	94dB	97dB
Mounting Depth	2.50"		3.50"	3.50"	4.50"



Pro Audio Tweeters	SPT.05	SPT.06	SPT.20	SPT.22	SPD-200	SPD-300	SPD.400
MAX Power Handling	250w	350w	350w	600w	200w	300w	400w
RMS Power Handling	125w	175w	175w	300w	100w	150w	200w
Voice Coil & Diaphragm	1" Aluminum	1" Aluminum	1" Aluminum	1.75" Aluminum	1" Aluminum	2" Titanium	3" Titanium
Impedance	4-Ohm	4-Ohm	4-Ohm	4-Ohm	4-Ohm	4-Ohm	8-Ohm
Frequency Response	2kHz-20kHz	2kHz-25kHz	2kHz-20kHz	2kHz-25kHz	3kHz-20kHz	1.5kHz-20kHz	500Hz-25kHz
Efficiency (1w/1m)	104dB	102dB	105dB	106dB	101dB	107dB	110dB
Mounting Depth	2.00"	1.125"	2.125"	2.50"			7.50"

NEW FOR 2017 SOUNDSTREAM



Dual Display Source Unit

VRN-DD7HB
ISO 2-DIN GPS Navigation, DVD, CD/MP3, AM/FM Receiver w/ Dual 7" LCD Touch Screens, Android PhoneLink, & Bluetooth 4.0 Connectivity



1030 Series Source Units

VR-1032XB
ISO 2-DIN DVD, CD/MP3, AM/FM Receiver w/ Sirius/XM Tuner Interface, Bluetooth 4.0 Connectivity, & 10.3" LCD Touchscreen



aptiX 75 Series Source Units


VRN-75HXB - iGo GPS Navigation + Android PhoneLink + SiriusXM Tuner Ready + Standards
VRN-75HB - iGo GPS Navigation + Android PhoneLink + Standards
VR-75XB - SiriusXM Tuner Ready + Standards
VR-75B - Standard Features
 ISO 1-DIN DVD, CD/MP3, AM/FM Receiver w/ Bluetooth 4.0 Connectivity, & 7" Touchscreen LCD



65 Series Source Units

iGo GPS Navigation + Android PhoneLink + SiriusXM Tuner Ready - **VRN-65HXB**
 SiriusXM Tuner Ready + Standards - **VR-65XB**
 ISO 2-DIN DVD, CD/MP3, AM/FM Receiver w/ SiriusXM Interface, Bluetooth 4.0 Connectivity, & 6.2" Touchscreen LCD





63 Series Source Units

- VRN-63HB** - iGo GPS Navigation + Android PhoneLink + Standards
 - VR-63XB** - SiriusXM Tuner Ready + Standards
 - VR-63B** - Standard Features
- ISO 2-DIN DVD, CD/MP3, AM/FM Receiver w/ Bluetooth 4.0 Connectivity, & 6.2" Touchscreen LCD



- Android PhoneLink
- iGo primo
- Map updates
- SiriusXM Ready
- X300 WATT 4CH. AMPLIFIER
- AUX INPUT
- Bluetooth
- DVD
- TOUCH SCREEN
- USB

Multimedia Source Units

- VR-732B**
- IS 1-DIN DVD, CD/MP3, USB/SD, AM/FM Receiver w/ Bluetooth Connectivity & Motorized 7" Touchscreen LCD



- Bluetooth
- DVD
- X300 WATT 4CH. AMPLIFIER
- TOUCH SCREEN
- AUX INPUT
- USB

62 Series Source Units

- VR-624B**
- ISO 2-DIN DVD, CD/MP3, AM/FM Receiver w/ Bluetooth 4.0 Connectivity, & 6.2" Touchscreen LCD



- Bluetooth
- DVD
- X300 WATT 4CH. AMPLIFIER
- TOUCH SCREEN
- AUX INPUT
- USB

- SiriusXM Tuner Ready + Standard Features - **VR-345XB**
- ISO 1-DIN DVD, CD/MP3, AM/FM Receiver w/ Bluetooth Connectivity, & Detachable 3.4" LCD



- SiriusXM Ready
- DVD
- X300 WATT 4CH. AMPLIFIER
- Bluetooth
- AUX INPUT
- USB

Rear Seat Entertainment



- black - **VHD-99BK**
 - grey - **VHD-99GR**
 - beige - **VHD-99BG**
- Universal Replacement Headrest w/ DVD Player, & 9" LCD Touch Screen

- DVD
- USB
- IR Transmitter
- AV INPUT
- SD
- FM Transmitter



2ch. Wireless IR Headphone INCLUDED!!!

Tarantula AMPLIFIERS Nano



TARANTULA NANO	TN4.1200D	TN1.2000D	TN1.3000D
Max Power	1,200w	2,000w	3,000w
RMS Power 4Ω	100 x 4	450 x 1	650 x 1
RMS Power 2Ω	150 x 4	800 x 1	1,000 x 1
RMS Power 4Ω Bridged	300 x 2	1,000 x 1 (1Ω)	1,500 x 1 (1Ω)
Remote Gain Control	-	Included	Included
Dimensions (7.25"w x 2.25"h)	11.75"	12.75"	15.75"

STEALTH AMPLIFIERS

New in 2017, the Stealth family welcomes a 500w 2-channel, 500w 3-channel, 600w 4-channel, and a 500w mono-block!!!



Stealth Amplifiers	ST2.1000D	ST3.1000D	ST4.1200D	ST1.1000D
MAX Power	1,000w	1,000w	1,200w	1,000w
RMS Power 4Ω	140 x 2	65 x 2 + 1 x 200	100 x 4	350 x 1
RMS Power 2Ω	250 x 2	100 x 2 + 1 x 300	150 x 4	500 x 1
RMS Power 4Ω Bridged	500 x 1	200 x 1 + 1 x 300	300 x 2	-
Remote Gain Control	Included	Included	-	Included
Dimensions (3"w x 1.5"h)	6.50"	7.75"	7.75"	7.75"

ARACHNID AMPLIFIERS



ARACHNID AMPLIFIERS	AR4.1200	AR4.1800	AR1.2500D	AR1.4500D	AR1.8000D
MAX Power	1,200w	1,800w	2,500w	4,500w	8,000w
RMS Power 4Ω	120 x 4	180 x 4	500 x 1	900 x 1	1,500 x 1
RMS Power 2Ω	150 x 2	225 x 4	850 x 1	1,500 x 1	2,500 x 1
RMS Power 4Ω Bridged	300 x 2	450 x 2	1,250 x 1 (1Ω)	2,200 x 1 (1Ω)	4,000 x 1 (1Ω)
Remote Gain Control	-	-	Included	Included	Included
Dimensions (8.50"w x 2"h)	13.50"	15.75"	12.75"	13.75"	18.50"

Rubicon NANO AMPLIFIERS



Rubicon Nano	RN4.1400D	RN5.2000D	RN1.2000D	RN1.3000D	RN1.5000D
Max Power	1,400w	2,000w	2,000w	3,000w	5,000w
RMS Power 4Ω	125 x 4	75 x 4 + 300 x 1	400 x 1	600 x 1	1,000 x 1
RMS Power 2Ω	175 x 4	125 x 4 + 500 x 1	600 x 1	900 x 1	1,500 x 1
RMS Power 4Ω Bridged	350 x 2	250 x 2 + 500 x 1 (2Ω)	1,000 x 1 (1Ω)	1,500 x 1 (1Ω)	2,500 x 1 (1Ω)
Remote Gain Control	-	Included	Included	Included	Included
Dimensions: (6.50" w x 1.50"h)	9.00"	11.75"	9.00"	10.25"	13.75"

Amplifier Installation Complete D.I.Y. Installation Kits

- WKIT-0**
0AWG Installation Kit w/ 200A ANL Fuse
- WKIT-4**
4AWG Installation Kit w/ 120A MANL Fuse
- WKIT-8**
8AWG Installation Kit w/ 80A MANL Fuse



All Installation Kits Include:
 17ft Power Wire
 3ft Ground Wire
 25ft Speaker Wire
 17ft Twisted Pair RCA Interconnect
 17ft Remote Turn-on Wire
 MANL or ANL Fuse Holder w/ Fuse
 Complete Installation Accessories

Shop for other amplifiers on our website.

